

HASTELLOY® G-35® alloy

Specifications and Codes

Specifications		Codes	
HASTELLOY® G-35® alloy (N06035)		HASTELLOY® G-35® alloy (N06035)	
Sheet, Plate & Strip	SB 575/B 575 P= 43	Section I	-
Billet, Rod & Bar	SB 574/B 574 B 472 P= 43	Section III	Class 1 -
Coated Electrodes	SFA 5.11/ A 5.11 (ENiCrMo-22) F= 43	Section III	Class 2 -
Bare Welding Rods & Wire	SFA 5.14/ A 5.14 (ERNiCrMo-22) F= 43	Section III	Class 3 -
Seamless Pipe & Tube	SB 622/B 622 P= 43	ASME Section VIII	Div. 1 800°F (427°C) ¹
Welded Pipe & Tube	SB 619/B 619 SB 626/B 626 P= 43		Div. 2 -
Fittings	SB 366/B 366 SB 462/B 462 P= 43	Section XII	-
Forgings	SB 564/B 564 SB 462/B 462 P = 43	B16.5	800°F (427°C) ²
DIN	No. 2.4643 NiCr33Mo8	B16.34	800°F (427°C) ²
TÜV	-	B31.1	-
Others	NACE MR0175 ISO 15156 ASME Code Case No. 2484	B31.3	800°F (427°C)
		VdTÜV (doc #)	-

¹Plate, Sheet, Bar, Forgings, fittings, welded pipe/tube, seamless pipe/tube

²Plate, Bar, Forgings, seamless pipe/tube