



Haynes International is a full-service manufacturer of high-performance nickel alloy wire products. No matter what size your order is, our highly trained sales staff and technicians will provide end-use technical support and customer service.



Haynes Wire Products
Phone: 1-800-354-0806
or 765-456-6012
Fax: 765-456-6079
 158 N. Egerton Road
 P.O. Box 677
 Mountain Home, NC 28758-0677



Corrosion-Resistant Alloys*			Specifications	
Alloy	UNS	AWS/ASME	AMS	Other
HASTELLOY® B-3®	N10675	ERNiMo-10		
HASTELLOY® C-4	N06455	ERNiCrMo-7		
HASTELLOY® C-22®/622	N06022	ERNiCrMo-10		
HASTELLOY® C-22HS®	N07022			
HASTELLOY® C-86	N06686	ERNiCrMo-14		ASTM B574
HASTELLOY® C-276	N10276	ERNiCrMo-4		
HASTELLOY® C-2000®	N06200	ERNiCrMo-17		
HASTELLOY® G-30®	N06030	ERNiCrMo-11		
HASTELLOY® G-35®	N06035	ERNiCrMo-22		ASTM B574
HAYNES® 200	N02215	ERNi-CI		
HAYNES® M400	N04400		AMS 4730	QQ-N-281
HAYNES® M413	C71580	ERCuNi		
HAYNES® M418	N04060	ERNiCu-7		
HAYNES® N61	N02061	ERNi-1		
ULTIMET®	R31233			ASTM B815

High-Temperature Alloys*			Specifications	
Alloy	UNS	AWS/ASME	AMS	Other
HASTELLOY® S	N06635		AMS 5838	
HASTELLOY® W	N10004	ERNiMo-3	AMS 5786	
HASTELLOY® X	N06002	ERNiCrMo-2	AMS 5798	
HAYNES® X-750	N07069	ERNiCrFe-8	AMS 5778	
HAYNES® 25	R30605		AMS 5796	
HAYNES® 82	N06082	ERNiCr-3	AMS 5836	
HAYNES® 188	R30188		AMS 5801	
HAYNES® 214® (Structural)	N07214			Structural Grade
HAYNES® 214-W (Weld Grade)				Weld Grade
HAYNES® 230-W®	N06231	ERNiCrWMo-1	AMS 5839	
HAYNES® 242®	N10242	ERNiMo-12		
HAYNES® 263	N07263		AMS 5966	
HAYNES® 282®	N07208			
HAYNES® 556®	R30556	ER3556	AMS 5831	
HAYNES® 600	N06600		AMS 5687	ASTMB166
HAYNES® 617	N06617	ERNiCrCoMo-1		
HAYNES® 625	N06625	ERNiCrMo-3	AMS 5837	
HAYNES® 718	N07718	ERNiFeCr-2	AMS 5832	
HAYNES® HR-120®	N08120			ASTMB408
HAYNES® HR-160®	N12160	ERNiCoCrSi-1		
MULTIMET®	R30155		AMS 5794	
HAYNES® Waspaloy	N07001		AMS 5828	

Coated Electrodes*			Specifications	
Alloy	UNS	AWS/ASME	AMS	Other
HASTELLOY® B-3®	W80675	ENiMo-10		
HASTELLOY® C-4	W86455	ENiCrMo-7		
HAYNES® C-22®/122	W86022	ENiCrMo-10		
HASTELLOY® C-276	W80276	ENiCrMo-4		
HASTELLOY® C-2000®	W86200	ENiCrMo-17		
HASTELLOY® G-30®	W86030	ENiCrMo-11		
HASTELLOY® G-35®	W86035	ENiCrMo-22		
HASTELLOY® X	W86002	ENiCrMo-2		
HAYNES® 112	W86112	ENiCrMo-3		625 core
HAYNES® 117	W86117	ENiCrCoMo-1		617 core
HAYNES® 182	W86182	ENiCrFe-3		
HAYNES® 230-W®	W86231	ENiCrWMo-1		
MULTIMET®	W73155	E3155	AMS 5795	
ULTIMET®	R31233			

*Other alloys available upon request

KENBLATT WELD INSTRUCTION
 Available Upon Request

ISO9001
CERTIFIED

AS: 9100
CERTIFIED

Approved for
Pratt & Whitney LCS

Approved for
Rolls Royce RR9000: SABRE

Standard Sizes

Welding Consumables

Wire Rod

Loose Coil* Diameters

in.	mm.
0.030	0.76
0.031	0.80
0.035	0.89
0.039	1.00
0.045	1.10
0.047	1.20
0.062	1.60
0.078	2.00
0.093	2.40
0.125	3.20
0.156	4.00
0.187	4.70

Precision Layer Wound RTW™ Wire Diameters

in.	mm.
0.030	0.76
0.031	0.79
0.035	0.89
0.039	1.00
0.045	1.10
0.047	1.20
0.062	1.60
0.078	2.00
0.093	2.40

Cut Lengths (GTAW)* Diameters

in.	mm.
0.030	0.76
0.031	0.79
0.035	0.89
0.039	1.00
0.045	1.10
0.047	1.20
0.062	1.60
0.078	2.00
0.093	2.40
0.125	3.20
0.156	4.00
0.187	4.70

Coated Electrodes Diameters

in.	mm.
0.093	2.40
0.125	3.20
0.156	4.00
0.187	4.70

Wire Rod for Redraw*

in.	mm.
0.218	5.50
0.250	6.40
0.256	6.50
0.275	7.00

HRAP
(Hot Rolled,
Annealed & Pickled)

*Other sizes available upon request



The GIMAX Precision Winder produces high-quality layer wound welding spools.

Thermal Spray Alloys

Specifications

Alloy	UNS	AWS/ASME	AMS
HAYNES® 20CB3	N08021	ER320/320LR	
HAYNES® 72	N06072	ERNiCr-4	
HAYNES® 80/20	N06003		ASTMB344
HAYNES® 95/5	N03301		
HAYNES® 200	N02200	ERNi-C1, UNS N02215	ASTMB160
HAYNES® 202	S20200	W-FeCrNi-3, UNS S20281	
HAYNES® 316L	S31603		ASTM A580
HAYNES® 420	S42000	ER420	
HAYNES® 625	N00625	ERNiCrMo-3	AMS 5837
HAYNES® C-276	N10276	ERNiCrMo-4	

All trademarks are owned by Haynes International, Inc.



Wire is available in loose coil form in standard diameters. Please contact the sales department for non-standard requests.

What is the RTW™

- The RTW™ finish is a proprietary surface finish engineered to offer more weld time and less maintenance time.
- RTW™ welding wire offers smooth feeding through welding machines, guns, and torches. The result is fewer arc outages, less downtime for tip/liner replacements, and reduced tip wear.
- Due to the extremely clean finish of RTW™ wire, less time is spent brushing or grinding.

The RTW™ finish is standard on all precision layer wound wire.




GTAW wire is precision cut and alloy verified prior to shipment.




Rigorous positive material identification checks are built into every product.

Photos of Welding Wire Magnified



Haynes Wire Products RTW™ welding wire



A competitor's welding wire

HAYNES International

Need help deciding which Haynes Wire product to use? Our on-line Welding SmartGuide helps with filler metal selections for various combinations of base materials. For your Local sales office or service center please call or visit our website.

Haynes Wire Products
Phone: 1-800-354-0806 or 765-456-6012
Fax: 765-456-6079